



DESCRIPTION Its delicate, light burnished brass, polished or matte black nickel composition forms luminous intersections, delineating the surrounding space with light. Spear Ceiling fills spaces with an elegant presence, combining light diffused from its Murano blown glass sphere with LED light. Also available in a suspended version.

PRODUCTS DETAILS

FUNCTION	CEILING
LOCATION	INTERIOR
LIGHT EMISSION	INDIRECT DOWNWARD LIGHT
LIGHT SOURCE	STRIP LED 15W/m 2700°K 1900lm/m CRI 80+ 24Vdc TOT. = 13,5W 1710lm + 1 × MAX 5W G9 LED 350lm 2700°K
ENERGY EFFICIENCY	G
RATED VOLTAGE	110 - 120 V / 220 - 240 V
FREQUENCY	50 - 60Hz
SUPPLY	TERMINAL BLOCK
BALLAST	BALLAST INCLUDED

DALI or TRIAC dimming kit available upon request

CERTIFICATION



MATERIALS

STRUCTURE	
M04	POLISHED BLACK NICKEL
M07	MATTE BLACK NICKEL
M11	LIGHT BURNISHED BRASS

PACKAGE

QTY	DIMENSIONS	NET WEIGHT	GROSS WEIGHT	TOTAL VOL.
1 × BOX	170 × 48 × H 30 cm (66"9 × 18"9 × H 11"8)	4 kg	8,5 kg	0,24 m ³

DIMENSIONS

